

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Atty. Docket: BARRE1

In re Application of:	)	Conf. No.:	3901
Luc BARRE	)		
	)		
IA No.: PCT/BE03/000231	)		
	)	Washington, D.C.	
IA Filed: December 24, 2003	)		
	)		
U.S. Appln. No.: 10/541,770	)		
Date: July 8, 2005	)	April 17, 2008	
	)		
For: METHOD AND APPARATUS...	)		

PRELIMINARY AMENDMENT

Customer Service Window, Mail Stop Amendment  
Honorable Commissioner for Patents  
U.S. Patent and Trademark Office  
Randolph Building, 401 Dulany Street  
Alexandria, Virginia 22314

Sir:

Prior to responding to the outstanding restriction  
requirement, please amend as follows:

**Amendments to the Claims** are reflected in the listing of  
claims which begins on page 2 of this paper.

**Remarks** begin on page 10 of this paper.

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) Method of manipulating heavier than air gas in a chamber, comprising

- successive opening and closing of the chamber, at the top thereof,

- introduction of the said heavy gas into the chamber in the closed position thereof and stoppage of said introduction in the open position of the chamber, and

- establishment of a negative pressure periphery at the top of the chamber with suction of heavy gas escaping through the top of the chamber to a confined enclosure.

2. (Original) Method according to Claim 1, characterised in that the opening of the chamber controls a stoppage of the said introduction and the closure of the chamber allows introduction of the said heavy gas into the chamber.

3. (Original) Method according to Claim 1, characterised in that a stoppage of the said introduction allows an opening of the chamber and a closure of the chamber allows an admission of the said heavy gas into the chamber.

4. (Previously presented) Method according to claim 1, characterised in that, after an initial closure of the chamber, the introduction of heavy gas effects a saturation of the chamber with this gas and in that, after each following closure of the said succession of closures and openings from the top, it comprises an additional introduction of heavy gas into the closed chamber.

5. (Previously presented) Method according to claim 1, characterised in that the establishment of the negative pressure is continued throughout the process.

6. (Previously presented) Method according to claim 1, characterised in that it comprises, at the bottom of the chamber, around it, a recovery of heavy gas flowing along the chamber from top to bottom.

7. (Previously presented) Method according to claim 1, characterised in that the heavy gas is a narcotic gas.

8. (Currently amended) Apparatus for manipulating heavier than air gas, comprising

- a chamber (1) having a closable cavity (2),

- a source of heavy gas (4) ~~which can~~ adapted to be in communication with the chamber ~~and to~~ allow introduction of the heavy gas into ~~its~~ the cavity, and

- a means (6, 7) of controlling the said communication between the source (4) and the cavity (2) of the chamber,

~~characterised in that~~ wherein the chamber (1) comprises an upward opening, and closure means (3) ~~able to be moved~~ movable between a closed position in which ~~they close~~ off the ~~said~~ upward opening is closed and an open position in which the ~~latter~~ opening is left clear,

~~in that~~ wherein the said control means (6, 7) are capable of passing from a stopped state to a state of leaving the ~~said~~ communication clear and vice versa, the said control means (6, 7) being in the stopped state when the ~~above-mentioned~~ closure means (3) are in an open position, and the said closure means (3) being in a closed position when the said control means (6, 7) are in ~~their above-mentioned~~ a clear state, and

~~in that it also comprises~~ a negative pressure source (35) and means of establishing a negative pressure (17) in a peripheral area at the top of the chamber, which are supplied by the negative pressure source and which suck heavy gas

escaping from the chamber (1) through the top into a confined enclosure.

9. (Original) Manipulation apparatus according to Claim 8, characterised in that it also comprises, in an external peripheral area at the bottom of the chamber (1), means (11) of recovering heavy gas flowing along the chamber from top to bottom.

10. (Previously presented) Manipulation apparatus according to claim 8, characterised in that the means of establishing a negative pressure function continuously.

11. (Previously presented) Manipulation apparatus according to claim 8, characterised in that the said control means comprise a stop valve (6) arranged in a pipe (5) connecting the heavy gas source (4) and the cavity (2) of the chamber, and a control element (7) for the valve which is locked mechanically in the above mentioned stopped state when the above mentioned closure means (3) are in the open position and which mechanically locks the closure means (3) in the closed position when it is in a release state.

12. (Previously presented) Manipulation apparatus according to claim 8, characterised in that the said control means comprise a stop valve (6) arranged in a pipe (5)

connecting the heavy gas source (4) and the cavity (2) of the chamber, and a control member which automatically locks the valve in the stopped state when it detects an output signal from the closure means outside their closure position and which automatically locks the closure means in the closed position when the valve is in a release state.

13. (Previously presented) Manipulation apparatus according to claim 8, characterised in that the said control means comprise a stop valve (6) arranged in a pipe (5) connecting the heavy gas source (4) and the cavity (2) of the chamber, and a control member which automatically locks the valve in the stopped state when it detects an output signal from a closure means outside their closure position and which is capable of controlling the valve in the release state when the closure means are in the closed position.

14. (Previously presented) Manipulation apparatus according to claim 8, characterised in that the closure means consist of a cover (3) sliding in a runner (15) provided at the upward opening of the chamber (1).

15. (Previously presented) Manipulation apparatus according to Claim 8, characterised in that the means of establishing a negative pressure comprise a frame (17) formed by a hollow profile which is supported by the chamber at the

periphery of its upward opening and which, on three sides (21-23), 23), overhangs part of the cavity (2) of the chamber and therefore the cover (3) in the closed position, whilst, on a fourth side (25), it is subjacent to a cover in the closed position, and in that the said hollow profiled section is provided, facing the cover in the closed position, with suction openings (24, 28), whilst it is in communication with the said source of negative pressure through an appropriate pipe (30).

16. (Previously presented) Manipulation apparatus according to claim 9, characterised in that the said recovery means comprise a trough (18) open upwards and a support plate (8) for the chamber (1) which is supported essentially in the trough at a distance therefrom.

17. (original) Manipulation apparatus according to Claim 16, characterised in that the trough has negative pressure means which act below the support plate and suck the heavy gas recovered by the trough.

18. (currently amended) Apparatus according to claim 16, characterised in that it also comprises, alongside the trough (11) provided with a support plate (8) for the chamber (1), at least one supplementary trough (36) each provided with



a support plate (37) for another chamber and/or for a body carrying heavier than air gas.

19. (Previously presented) Manipulation apparatus according to claim 9, characterised in that the means of establishing a negative pressure function continuously.

20. (Previously presented) Method according to claim 5, characterised in that the heavy gas is a narcotic gas.

21. (New) Apparatus for manipulating heavier than air gas, comprising

- a chamber (1) having a closable cavity (2),
- an upward opening of said chamber (1) with a closure (3) capable of being moved between a closed position in which the upward opening is closed and an open position in which the upward opening is left clear,
- a source of heavy gas (4) adapted for communication with the chamber to allow introduction of the heavy gas into the cavity (2),
- a negative pressure source (35) and a negative pressure means for establishing a negative pressure (17) in a peripheral area at the top of said chamber (1), supplied by said negative pressure source (35), which negative pressure



means (17) sucks heavy gas escaping from the chamber (1) through the top into a confined enclosure, and

- control means (6, 7) for controlling said communication between said heavy gas source (4) and said cavity (2) of said chamber (1), the control means (6, 7) being capable of passing from a stopped state to a state of leaving said communication clear, and vice versa, with said control means (6, 7) being in the stopped state when said closure means (3) is in an open position, and with said closure means (3) being in a closed position when said control means (6, 7) are in a clear communication state.

REMARKS


The above preliminary amendment is made to place claim 8 in better form for U.S. practice, and to add a second independent apparatus claim 21.

The applicant will file a timely reply to the outstanding restriction requirement Office Action.

Respectfully submitted,

BROWDY AND NEIMARK, P.L.L.C.  
Attorneys for Applicant

By



Sheridan Neimark  
Registration No. 20,520

SN:tdd

Telephone No.: (202) 628-5197

Facsimile No.: (202) 737-3528

G:\BN\G\geve\BARRE1\PTO\2008-04-17PREL AMDPCT FORMAT.doc